

StealthTouch-M5 Touchcomputer

fanless, compact, and versatile

StealthTouch-M5 is a 15" All-in-one touchcomputer powered by Intel Pentium-M technology. Its versatile design allows you to customize the M5 to meet your application requirements and budget.

When configured as fanless and diskless thin client, the M5 will reduce grease and dust intakes, therefore extending its life. It also has the power to run demanding applications in Windows XP or Vista. In certain environment, you may need to use different touch technology. The M5 offers you the choice of Resistive, Intellitouch SAW, or InfraRed touch to fit into specific environment for your application.

The M5's compact footprint will save counter space, it can also be mounted on the wall or a VESA pole. Utility devices can be integrated without adding footprint, such as WiFi wireless network, magnetic card reader, biometric fingerprint reader, and customer display. The M5's versatility makes it an ideal choice for applications in food service, retail, manufacturing, healthcare, and self-service kiosk.



Specifications

Display	15" LCD, Active matrix TFT, 1024x768
Touchscreen Option	Resistive, Intellitouch SAW, InfraRed
Processor	Intel Celeron-M 1GHz, upto Pentium-M 1.7GHz
Memory	256MB, upto 1GB DDR2
Video Memory	upto 128MB (shared)
Storage	Hard Drive, Solid-state Disk, or Compact Flash
CD/DVD	Internal (optional)
Operating System	XP Prof, WePOS, XP embedded, CE.NET, Linux
Network/Ethernet	10/100/1000 BaseT
WiFi (wireless)	RF 802.11 (optional)
Serial Port	4
USB 2.0	6 : 4 Standard, 2 powered +12V, 1 powered +24V
Parallel Port	1
Cashdrawer Port	2 (Epson emulation, 24V)
CF Slot	1 (optional)
Speakers	2 Watts, Stereo (optional)
Mounting Options	Wall or Pole mount, VESA 75mm
Security Lock	Bolted (4mm screw), or Kensington MicroSaver
Bezel Color	Dark grey
Dimensions (with Base)	Width: 14.63" (380mm) Height: 14.37" (373mm) Depth: 10.37" (269mm)
Weight	22 lbs / 10 kgs (10 lbs / 4.6 kgs without base)
Operating Temperature	0° C to 40° C
Operating Humidity	20% to 80%
Power Supply	External, 120W, AC 100-240V
Agency Approvals	FCC A, CE, UL
Add-ons	Magnetic stripe reader Barcode slot reader Fingerprint reader Rear customer display, Serial



VESA mount



Rear display

Product by



PioneerPOS, INC.

www.pioneerpos.com

888.468.9757