

Integrated Security Devices

ST-1275 Smart Terminal Smart Card Reader



**Dual Smart
Card Reader for
Contact and
Contactless Cards**

Main Applications

Desktop

Access Control
Logical and Network Logon
Single Application Sign-On
Convenient Replacement
for Passwords
3-Factor Authentication
Loyalty and Multi-Application Cards
PKI (Private Key Infrastructure)
Digital Signature
Document Encryption
Secure Payment for B2B and B2C

Target Markets

Public Administration
E-Government
Military (CAC)
Border Control
Transportation
Education
Financial
Point-of-Sales

Key Features

- USB 2.0 – dual smart card reader for contact and contactless cards
- One-hand operation with stable stand

Smart Card Reader

- PC/SC
- ISO 7816 compliant
- CT-API and OCF support
- T=0, T=1, S=8, S=9, S=10
- EMV 2000 Terminal Level 1 compliant
- CCID compatible

Contactless Smart Card Reader

- ISO 14443A / B compatible
- Dual LED Status indicator
- T=CL, Mifare
- Reading distance: <5 cm
- ICAO compliant

Integrated Security Devices

ST-1275 Smart Terminal Smart Card Reader



ST-1275UAE

Technical Data

Smart Card interface:

- Reads and writes all ISO 7816 cards
- Supports T=0, T=1, I²C (S=8), 2-wire (S=10), 3-wire (S=9)

Drivers:

CCID, PC/SC, CT-API

Card connecting unit:

Approx. 100,000 insertions sliding contacts

Smart Card speed:

412,903 bps

Clock frequency smartcard:

4.8 MHz

Weight:

Approx. 80 g (Smart Terminal)

Dimensions:

Approx. 105 x 70 x 12 mm

Cable length:

Approx. 1.75 m

Operating systems

Windows 2000, XP, XP 64Bit, Vista, Vista 64, Linux

System requirements

USB Interface 2.0

Approvals

GS/VDE, cRUus, CE, FCC, C-Tick Mark, GOST-R
Microsoft WHQL Windows™ 2000, XP, Vista
EMV 2000 Level 1

Current consumption:

Max. 100 mA

Interface:

USB

Storage temperature:

-20 °C to 50 °C

Operating temperature:

0 °C to 60 °C

Delivery volume

1 Smart Terminal

Packaging unit (Bulk):

250 pcs. per master carton
4 cartons per pallet (1000 pcs.)

Guarantee period:

2 years

Ordering Description

Order Number	Housing	Packaging	Language Packaging
ST-1275UAF	light grey	bulk	—
ST-1275UAE	black	bulk	—

Contact

Call, fax or visit our website for more information.

Cherry Electrical Products

11200 88th Avenue
Pleasant Prairie, WI 53158
Phone: 262.942.6500
Web: www.cherrycorp.com

E-Mail: sales@cherrycorp.com
Fax: 262.942.6566

Last Update: 8/8/08

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.