

# OPN2001

Pocket memory scanner



### + Related products



#### OPN2002

- Data Collector
- Pocket memory scanner
- USB, Bluetooth



#### OPL9725

- Data Collector
- Barcode laser scanner
- IrDA
- 1 key operation



#### DCL1530

- Data Collector
- Barcode laser scanner
- USB, IrDA
- Dry cell battery

## Operation

- CPU: ARM7 32-bit
- O/S: Proprietary
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

## Memory

- FlashROM: 512 kB (Program storage + >15.000 barcodes + time stamp)
- RAM: 64 kB

## Operating indicators

- Visual: 1 LEDbar (red/green/orange)
- Non-visual: Buzzer

## Operating keys

- Entry options: 2 keys total,
  - 1 clear key,
  - 1 scan key

## Communication

- USB: Mini USB, Ver. 1.1, VCP

## Power

- Rechargeable battery: Lithium-Ion 3.7V 150mAh
- Operating time: 1.000 scans (1 scan / 5 sec)
- Data retention time: Ca. 72 hours
- Charging method: Enclosed USB cable
- Battery charging time: Ca 2.5 hours

## Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Vibrating mirror
- Scan rate: 100 scans/sec
- Reading pitch angle: -30 to 0°, 0 to +30°
- Reading skew angle: -50 to -8°, +8 to +50°
- Reading tilt angle: -20 to 0°, 0 to +20°
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9 UPC
  - 60 - 570 mm / 2.36 - 22.44 in (1.0 mm / 39 mil),
  - 40 - 360 mm / 1.57 - 14.17 in (0.5 mm / 20 mil),
  - 40 - 220 mm / 1.57 - 8.66 in (0.25 mm / 10 mil),
  - 40 - 120 mm / 1.57 - 4.72 in (0.15 mm / 6 mil),
  - 50 - 100 mm / 1.97 - 3.94 in (0.127 mm / 5 mil)

## Supported Symbologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey-UK/Plessey, S-Code, Telepen, Tri-Optic
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: MicroPDF417, PDF417

## Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Ambient light immunity: White 3,000 lx max, Fluorescent 3,000 lx max, Direct sun 50,000 lx max
- Protection rate: IP 42

## Physical

- Dimensions (w x h x d):
  - 32 x 62 x 16 mm / 1.26 x 2.44 x 0.63 in
- Weight body: Ca. 28 g / 1 oz (incl. battery)
- Case: ABS, Black

## Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

## Enclosed items

- USB cable
- Neck strap

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp  
- **France:** Issy Les Moulineaux  
- **Germany:** Dietzenbach  
- **Italy:** Castel Maggiore (BO)  
- **Spain:** Valencia  
- **Sweden:** Järfälla  
- **United Kingdom:** Luton, Bedfordshire  
- **U.S.A.:** Renton, WA  
- **Japan:** Warabi City

- **Taiwan:** Taipei  
- **P.R.China:** Shanghai  
- **Australia:** Kariong  
- **Brazil:** São Paulo

Opticon, Inc.  
2220 Lind Avenue SW  
Suite 100  
Renton, WA 98057  
Toll Free: (800) 636-0090  
Local: (425) 651-2120  
Fax: (425) 454-0865  
Email: sales@opticonusa.com

**OPTICON**USA

WWW.OPTICONUSA.COM