

Delivering Technology with Style

HT - 2000 / 4000 Series



The HT Series Integrated Retail System by POSIFLEX is a PC-based compact POS terminal, designed and developed for use in the retail and service sectors. The integrated LCD touch monitor can be easily adjusted and is removable. A PCI Slot is available for added functionality. Power management functions include software controlled ON/OFF switch and optional internal UPS battery to insure proper shutdown of the system to protect against data corruption. Options include a combination MSR and biometric finger print attachment and VFD customer pole display or secondary LCD panel for promotions/advertising. All HT models service multiple markets, including: hospitality, retail, gaming, kiosk, healthcare, c-store, grocery, etc.

POSIFLEX™



ALL HT SERIES TERMINAL MODELS CAN BUNDLE WITH

- SD300 Series 2-in-1 Attachment MSR and/or U.are.U Finger Print Sensor
- CR4000 / CR6000 Series Cash Drawer
- PP7000 Series Aura Thermal Receipt Printer
- PD2601 Pole Display
- KB6000 Series Programmable Keyboard

Specifications

Model	HT- 2212	HT- 4212
Max. LCD Resolution:	800 x 600 or 1024 x 768 (option)	
Brightness:	180 nits (350 nit optional)	
LCD Panel:	12.1" Color TFT LCD	
Touch Sensor:	Resistive type	
CPU (Ultra DMA):	VIA C7 1.0 GHz	Celeron 2.0 GHz
Memory:	128 MB (expandable to 2 GB)	256 MB (expandable to 2 GB)
Video Memory:	16~64 MB shared memory	
Audio Line Input:	1	
Audio Line Output:	1 (Booster required for speakers)	
PCI slot:	1	
Serial Port:	2	4
Parallel port:	1	
CR Port:	1	1 option, Included in Power Management Kit
Power USB Ports:	NA	Proprietary control card, Optional
USB Port:	6	3
KB Port:	1 x PS/2 type	
Mouse Port:	1 x PS/2 type	
Lan Port:	10/100 MHz base Ethernet	
VGA Port:	One external VGA monitor port for 2nd screen	
HDD:	40 GB	
FDD:	Option available for USB interface	
OS Support:	XP Professional / WEPOS	
Internal UPS:	Yes (Battery Optional)	
Tilt Adjustment:	From 17.5° to 87.5°	
Power Supply:	Input 100~23/40V, output DC 12V/80W	Input 115~230V, output DC180W
Housing Color:	Black / Charcoal	Charcoal
Dimension:	Base: 10.6"(W) x 9.5"(D) x 4.0" (H) Panel: 11.3"(W) x 8.9"(H)	
Weight:	5.45 Kg (12 lbs.)	6.5 Kg (14.3.9 lbs.)
Safety Certifications:	Power Supply: UL, TUV, Terminal: CE, FCC Class A	

About POSIFLEX

POSIFLEX is a leading manufacturer of all-in-one touch based systems and related peripherals serving the point-of-service market segments. POSIFLEX designs and produces products in two ISO 9001/9002/14001 certified factories in Taipei, Taiwan and has been awarded several patents worldwide for its innovative product design. POSIFLEX products include the KS 'Fan-Free' terminal series, the award winning JIVA terminal series, thermal receipt printers, displays, scanners, kitchen video systems, keyboards, signature capture devices, mobile terminals, cash drawers and more. All products carry a standard three-year warranty. Founded in 1984, POSIFLEX is a global company with principal offices in the United States, Europe and Taiwan. For more information, visit www.posiflexusa.com.

Features



MSR 2-in1 Attachment with optional U.are.U finger print sensor (SD-300)



A patented finger release lever "Gear Lock" mechanism easily adjusts the LCD tilt angle from 42.5° to 77.5°



Cable management design allows easy routing of cables for aesthetic and reliability purposes



Ergonomic design allows LCD display swivel angle 0° to 16° in clockwise direction for improved viewing angles

HT-2000/4000 POS service features



Place finger underneath each corner of rear cable cover and remove



Step 2

Access to mainboard

Press buttons on each side of metal chassis and lift system cover



Step 3

Press metal spring clip to access hard drive.

POSIFLEX™

e-mail: sales@posiflexusa.com
www.posiflexusa.com