



XT3815

KEY FEATURES

- Intel[®] Celeron[™] J1900 / 2.0GHz
- 2GB DDR3L memory (8GB maximum)
- Projected Capacitive touch
- Fan Free
- USB 3.0 support
- Digital Brightness Control
- VESA mount capability
- Slim, folding base design
- Optional Solid State Drive and WiFi
- Optional Upgrade Kits
 - Powered USB Kit
 - (1) 24V USB 2.0 Port and (3) 12V USB 2.0 Ports
 - Powered USB base can house power adapter and backup battery with 150W power supply
 - 8-Port USB Hub Kit
 - (8) port USB hub with 150W power supply

About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- · Global presence
- Two ISO 9001/9002/14001 Certified Facilities

Performance at Exceptional Value

The XT3815 is a cost-effective workhorse, ideal for environments where cost is a factor, but performance cannot be compromised either. Backed by field-tested reliability, the XT3815 inherits the long legacy of quality that only Posiflex can deliver.

The XT3815 base conveniently folds and configures to an optimal angle and space for various types of environments. The low-profile design fits in the tightest of spaces, reducing shipping costs up to 40%. With this sleekly designed exterior comes the Intel[®] Celeron[™] 2.0GHz power to run many applications for hospitality, retail, health care and more.

The XT3815 features an Intel[®] Celeron[™] J1900 / 2.0GHz, 2GB standard DDR3L RAM (8 GB maximum) and a 15" projected capacitive touch TFT LCD touch screen terminal. Along with a rich array of connectivity features are options for a mini-PCle slot for WiFi and VESA wall mount bracket.

Specifications	XT3815	
Processor	Intel® Celeron™ J1900 / 2.0GHz	
System Memory	DDR3L SO-DIMM x 1, max. 8GB, factory default 2GB	
Storage Device	320GB HDD SSD Available	
Supported OS	POSReady 7 / Windows 7 Professional / Windows Embedded 8.1 Industry	
Touch	Projected Capacitive	

Physical Dimensions

Dimensions (WxDxH) in.	14.6" x 12.5" x 9.9"
Display	15" LED-backlit TFT LCD,1024x768
Weight (lbs)	12.3

Connectivity	
LAN Port	1 x Gigabit LAN Port
Serial Port	1 x RJ-50 Serial 3 x DB9 Serial
VGA Port	1 x VGA Port
USB 2.0 Port	6 x (5) on I/O Panel (1) on Power Side
USB 3.0 Port	1 x on I/O Panel
12v Battery port	1 x Proprietary port used with the RB2000
Mini-PCle slot	1
CR PORT	1 x (Controls 2 Drawers) Dual Independent Sensor COM1/COM5 Select

Options

Parallel Port with optional extension cable

WB-5000 wall mount

bracket WiFi

Parinharals

Peripherais	
WB5000	Wall mount bracket
Upgrade Kits	Powered USB Upgrade Kit - (1) 24V USB 2.0 Port plus (3) 12V USB 2.0 Ports with 150W power supply 8-Port USB Hub Kit - (8) port USB hub with 150W power supply
PD2605X00FEP	2X20 VFD rear-mount pole display
PD2605W00FEP	2X20 VFD rear-mount pole display
PD2608UE011	2X20 VFD rear-mount customer display
RB2000	Backup battery
SA105100	3 track encryption capable without finger print reader
SA30520100	3 track encryption capable with finger print reader
LM3010000	9.7" rear-mount secondary display
LM3015000	15" rear-mount secondary display

^{**} The product information and specifications are subject to change without prior notice.






















Available Services

up to 5 years.

Posiflex.

repairs.

 OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process.

• Regional Repair Depots Three regional depots assure fast turn-around time on

• Post Warranty Support Spare parts, in addition to a flat rate repair program, for post warranty needs.

Installation Services

your equipment.

Team helps design

equipment, for custom hardware applications.

Let our nationwide network of experts stage and install

• OEM Design and Integration

Our Product Development

 Advance Exchange We ship overnight replacement equipment directly to your business. You return the faulty unit to

 Standard and Extended Warranty Extend your depot warranty

> P: 888-968-1668 F: 510-475-0982 sales.department@posiflexusa.com www.posiflexusa.com

Posiflex Business Machines, Inc.

Posiflex designs, engineers and manufactures: